

GS2054DH

Standard smart lithium battery pack 14.4V/3450mAh/47.52Wh



Feature

- Worldwide approvals and certification of safety standards.
- Smart batteries with numerous features according to the SMBus specification.
- Integrated LED state of charge (SOC) indicator.
- Panasonic cells, highest energy density and stability.
- JEITA charging optimization rules.
- Comprehensive safety protection functions, such as overcharge, over-discharge, overcurrent, overtemperature, short circuit, etc.
- Balance function, effectively improve battery life.
- High precision Fuel gauge.

Application

Suitable for portable electronic equipment, industry and medical field.

Information

Factory capacity	20%~30%
Compliance information	CE/FCC/IEC62133/UN38.3/UKCA/PSE
Operating temperature	0°C~50°C (Charge) -20°C~60°C (Discharge)
Storage temperature	-20°C~50°C (Maximum) -20°C~25°C (Recommend)


Electrical parameters

Rated voltage	14.4V
Rated capacity	3300mAh
Nominal capacity	3450mAh
Internal resistance	< 200mΩ@1kHz at 25°C
Maximum charging current	1.65A
Maximum charging voltage	16.8V
Maximum discharge current	4.0A
Cycle life	500 cycles ≥ 80% Rated capacity

Dimensions

Length	85.1mm ± 0.3mm
Width	77.4mm ± 0.3mm
Thickness	22.7mm ± 0.3mm
Weight	235g±10g

Interface



Pin定义说明:

1	2	3	4	5
P+	SMBC	SMBO	T	P-

A
2:1

Recommended Accessories	Type	Product	Application
	Battery Mating Connector	GSC550M18012D GSC550M09010D	Mating connector for standard smart batteries from TEFOO. Available for 90° or 180° PCB mounting.
	SMBus Reader	GSSBR	No external power supply required. Simple read out of SMBus batteries data.
	Power Management Module	GSPMBSMBus	Recharge the battery and seamlessly switch between the adapter and battery power supply, Ready to use without development.
	Smart Battery Charger	GSCH4000A	Compliant with SMBus specification, compatible with all TEFOO smart batteries.
	Dual Smart Battery Charger	GSCH4040	Dual bay charger, Compliant with SMBus specification, compatible with all TEFOO smart batteries.
	Portable Battery Charger	GSCH054D	Small size, easy to carry, suitable for GS2054 series batteries.
	Battery Cable	GSSBC	Used for battery wiring, making it easy to quickly debug the power supply during the development phase.