

# GSP19V120W55250

双仓充电座适配器 Double-bin smart battery charger adapter  
P/N: 97010017

**19.5V / 6.15A / 120W MAX**



适用于充电座 (Suitable for charger) :  
GSCH4040

## 电性能 / Electrical

输入电压 / Input voltage	90- 265VAC
输入频率范围 / Input frequency range	47-63Hz
输出额定电压 / Output rated voltage	19.5V DC
输出额定电流 / Output rated current	6.15A
最大输出功率 / Maximum power	120W
转换效率 / Conversion efficiency	> 85%

## 安全与可靠性 / Safety and reliability

安全规范/ Safe	UL / CSA / CCC / BSM / PCBC / CE / FIMKO / DEMIKO / NEMIKO / SIMKO / TUV
电磁兼容/ EMC	IEC 61000-4.3 Radiated Immunity (RS), CISPR32 CLASS-B IEC 61000-4.6 Conducted Immunity (CS), CISPR32 CLASS-B EN55032 Class B EN610003-3

## 尺寸规格 / Dimensions

长 / Length	136mm ± 1.0mm
宽 / Width	68mm ± 1.0mm
厚 / Thickness	25mm ± 1.0mm
重量 / Weight	365g ± 10g

## 接口 / Interface

AC 输入 / AC input	梅花型三芯 (IEC 320, C6 CERTIFIED, 3 WAY)
AC 输入引线长度 / AC input lead length	1500 ± 30mm
DC 输出 / DC output	2.5φ x 5.5φ x 11.0 DC
DC 输出引线长度 / DC output lead length	1800 ± 50mm

