Dedicated Charger

Model: GSCH047D

Features

- > Lightweight and compact structure design.
- With power on, charge, full indicator light.
- Precharge constant current constant voltage safe and efficient charging management.
- Comprehensive safety protection functions, such as over charge, over current, over temperature, reverse connection, etc

Suitable Battery Model

Compatible with GSX047 series standard smart battery.

Fastcharge Safety Time

CE FC

Charge Characteristics

Fastcharge Current Regulation Phase

Charge

Precharg Current Regulatio

Phase

Charge Current

Precharge

Time

Regulation Voltage

Regulation Current

VLOWY

Key Parameters

Input voltage

| Input power | ≥28W |
|--------------------|---------------------|
| Input interface | DC φ2.1x5.5mm |
| Charging voltage | 8.4V |
| Charging current | 3A |
| Charging interface | +/C/D/T/- |
| Dimensions | 68.70*50.60*32.70mm |
| Weight | 60g±5g |
| LED Display | |
| left light on | Charging |

DC 10V~24V

| left light on | Charging |
|-----------------|---------------|
| Middle light on | Fully charged |
| Right light on | Power on |

Selection Of Accessories

| Recommended | Categories | Models | Purpose |
|-------------|---------------|-----------------|---------------------------------|
| | | | Input: AC 90V~264V |
| | | | Output: DC 19V/2.5A |
| | AC/DC Adapter | GSP19V048W55210 | Two pin plug optional: Chinese, |
| | | | American (Japanese), British, |
| | | | European (Korean), Australian |



TEFOO