

## Model: GSCH40

### ■ Features


- Wide voltage input.
- Follow SMBus v1.1 smart battery protocol.
- Intelligent identification of battery charging voltage and current, safe and efficient charging
- With power on, charging and full charge indicators.
- Full safety protection functions, such as over voltage, over current, reverse connection protection, etc.

### ■ Suitable Battery Model

Compatible with all TEFOO standard smart batteries.



### ■ Charge Characteristics



### ■ Key Parameters

	DC 9V~24V (Input voltage should be greater than the maximum charging voltage+1v required by the battery.)
Input voltage	
Input power	≥60W
Input interface	DC φ2.1x5.5mm
Charging voltage	0~16.8V (Adaptive 1~4 series smart battery)
Charging current	0~4A
Charging interface	+ / C / D / T / -
Dimensions	111.00*84.00*35.00mm
Weight	200g±10g



### ■ Certification Information



### ■ LED Display

Blue LED light	Power on
Green LED flashing	Charging
Green LED light	Fully charged
Red LED light	Charging fault

### ■ Selection Of Accessories

Recommended	Categories	Models	Purpose
	AC/DC Adapter	GSP24V060W55210	Input: AC 90V~264V Output: DC 24V/2.5A
	Car Adapter	GSCAR19V5525100W	Input: DC 12V~24V Output: DC 19V/5.2A